



# AirShield

ArcOne's new full-coverage grinding visor exceeds expectations with its durable construction, large viewing area, sturdy headgear, quick and easy visor installation and removal, all at an economical price-point.

Features include:

Use the AirShield® for sandblasting, grinding and painting

Complete with comfortable 04-HG sweatband

Adjustable Airflow Direction

The visor is 0.067inch thick

Will fit a hard hat (diminished sight line)

Visor dimension: 6.96inch x 5.42inch x 0.04inch, Viewing area: 41.2 sq. in. (176.9 mm x 137.7 mm x 1.0 mm, Viewing area: 26560 mm<sup>2</sup>)

Shell is 0.28 lbs (130 grams); Visor is 0.12 lbs (55 grams); Complete 0.58 lbs (265 grams)

Z87+ Impact Protection

Meets/Exceeds: ANSI Z87+, CAN/CSA Z94.3, CE EN 166

## More Photos



**AirShield**



**With Helmet**



**AIR-HEL**



**AIR-CL**



**AIR-WHA-  
04**



**AIR-WHA-  
10**

## Additional Product Information

### Part #

AIR-SH

AIR-HEL

AIR-CL

AIR-WHA-04

AIR-WHA-10

### Description

AirShield® Molded High-Impact Grinding Visor

AirShield® Replacement Shell Only

AirShield® Visor 2-Pack (8.75 x 5.5 x .040 Inches)

Adapter to attach AirShield® to an ArcOne® welding helmet with 04-HG

Adapter to attach AirShield® to an ArcOne® welding helmet with 10-HG