

## **AirShield**

ArcOne's new full-coverage grinding visor exceeds expectations with its durable construction, large viewing area, sturdy headgear, quick and easy visor installation and removal, all at an economical price-point.

Features include:

Use the AirShield® for sandblasting, grinding and painting

Complete with comfortable 04-HG sweatband

Adjustable Airflow Direction

The visor is 0.067inch thick

Will fit a hard hat (diminished sight line)

Visor dimension: 6.96inch x 5.42inch x 0.04inch, Viewing area: 41.2 sq. in. (176.9 mm x 137.7 mm x 1.0

mm, Viewing area: 26560 mm2)

Shell is 0.28 lbs (130 grams); Visor is 0.12 lbs (55 grams); Complete 0.58 lbs (265 grams)

**Z87+ Impact Protection** 

Meets/Exceeds: ANSI Z87+, CAN/CSA Z94.3, CE EN 166

## More Photos











**AirShield** 

With Helmet

**AIR-HEL** 

AIR-CL





AIR-WHA-04

AIR-WHA-10

## **Additional Product Information**

Part # Description

AIR-SH AirShield® Molded High-Impact Grinding Visor

AIR-HEL AirShield® Replacement Shell Only

AIR-CL AirShield® Visor 2-Pack (8.75 x 5.5 x .040 Inches)

AIR-WHA-04 Adapter to attach AirShield® to an ArcOne® welding helmet with 04-HG AIR-WHA-10 Adapter to attach AirShield® to an ArcOne® welding helmet with 10-HG